

# Postech

## 产品特性：

- 低功耗、性能强大
- 全面读取所有主流一维
- 二维码快速读取手机屏幕条码
- 支持RS232接口和USB接口

## 二维扫码枪HS20



# 技术规格书

物理特性	
尺寸Dimensions:	170mm x 95mm x 70mm
重量Weight:	155g
电压Voltage :	5VDC
电流Current :	80mA (standby); 300mA (Operating)
性能特点	
传感器像素Image (Pixels):	640 pixels (H)x 480 pixels (V)
光源Light Source:	Aiming: 617 nm LED; illumination: 6500K LED
视场角Field of View:	45° (H) x 35° (V)
旋转倾斜偏转Roll / Pitch / Yaw:	360°, ±65°, ±60°
打印对比度Print Contrast:	25% minimum reflective difference
接口支持Interfaces Supported:	USB, RS232
运动容差Motion Tolerances	up to 25 in. (63.5 cm) per second
识读码制	
一维条码1-D:	UPC, EAN, Code128, Code 39, Code 93, Code11, Matrix 2 of 5, Interleaved 2 of 5, Codabar, MSI Plessey, GS1 DataBar, China Postal, Korean Postal, etc.
二维条码2-D:	PDF417, MicroPDF417, Data Matrix, Maxicode, QR Code, MicroQR, Aztec, Hanxin, etc.
使用温度	
工作温度Operating Temperature:	0°C to 50°C
存储温度Storage Temperature:	-40°C to 70°C
湿度Humidity:	0% to 95% relative humidity,non-condensing
抗震性Shock Specifications:	Designed to withstand 1.5m(5') drops
环境光免疫Ambient Light Immunity:	100.000 Lux.
景深	
5MIL	20mm-70mm
13MIL	40mm-160mm
1D Minimal Resolution	4mil
Performance may be impacted by bar code quality and environmental conditions	